



Keyless Drill Chucks

TYPE: XHSP



SPECIAL HEAVY DUTY TYPE



OPTIONAL ACCES.

- Special design & manufacture against for super heavy torque(Clamping capacity) use.
- Owing to inspecting strictly & with excellent RUNOUT Accuracy and quality guanteed the gripping power is double than the general brand.
- Avoid the drill dropped when used in instaneous change of direction and equipped with spanner hole for tightening perfect safety.
- Especially suitable for CNC machining center & milling machine use.
- Accuracy: 50mm length within 0.05mm
- The key is optional

Unit:mm

ORDER NO.	TYPE	Clamping Capacity		Female Taper DIN or Jacobs	OUTER Ø / mm	Length		Wt g	QTY Pcs./ Cu-Ft	N.W/G.W kgs	CODE NO.
		Ø mm	Ø inch			Open B mm	Closed A mm				
11015	8XHSP	0-8	0-5 / 16"	B10	36	61	69	320	40/0.6	13/14	3302-002
11016				J1	36	61	69	320	40/0.6	13/14	3302-003
11017				B12	36	61	69	320	40/0.6	13/14	3302-004
11018	10XHSP	0-10	0-3 / 8"	J33	43	81	92	700	40/0.6	28/29	3302-005
11019				J2S	43	81	92	700	40/0.6	28/29	3302-006
11020				B12	43	81	92	700	40/0.6	28/29	3302-007
11021				B16	43	81	92	700	40/0.6	28/29	3302-008
11025	13XHSP	0-13	0-1 / 2"	J6	51.5	92	103	1030	30/0.6	31/32	3302-009
11026				J33	51.5	92	103	1035	30/0.6	31/32	3302-010
11027				B16	51.5	92	103	1030	30/0.6	31/32	3302-011
11028	16XHSP	3-16	1/8 - 5/8"	J6	58	95	108	1450	24/0.6	35/36	3302-012
11029				B16	58	95	108	1450	24/0.6	35/36	3302-013
11030				B18	58	95	108	1450	24/0.6	35/36	3302-014
11035				J3	58	95	108	1450	24/0.6	35/36	3302-015
17000	6XHSP	0.5-6.5	1/64" - 1/4"	B12	34	61	69	320	8/0.6	26/27	3304-010
17002				J1	34	61	69	320	8/0.6	26/27	3304-011
17004				B10	34	61	69	320	8/0.6	26/27	3304-012
11031	Key	13XHSP									3304-001
11032		16XHSP									3304-002
11033		8XHSP									3304-003
11034		10XHSP									3304-004



Keyless Drill Chucks

TYPE: H

STANDARD TYPE



Unit:mm

- Industrial design especially for life and safety while in operation.
- All hardened parts ensure long term for milling machines and drilling.
- Accuracy: 35 m/m length within 0.08 m/m

ORDER NO.	TYPE	Clamping Capacity		Female Taper DIN or Jacobs	OUTER Ø mm	Length		Wt g	CODE NO.
		Ø mm	Ø inch			Open B mm	Closed A mm		
11061	6H	0-6.5	0-1 / 4"	J1	34	61	69	410	3302-030
11062				B10	34	61	69	400	3302-031
11063	8H	0-8	0-5 / 16"	J1	34	61	69	400	3302-032
11064				B10	34	71	69	400	3302-033
11065	10H	0-10	0-3 / 8"	J2S	42.5	81	92	720	3302-034
11066				J33	42.5	81	92	700	3302-035
11067				B12	42.5	81	92	720	3302-036
11068				B16	42.5	81	92	700	3302-037
11070	13H	0-13	0-1 / 2"	J6	50.5	92	103	1070	3302-039
11071				J33	50.5	92	103	1035	3302-040
11072				B16	50.5	92	103	1080	3302-041
11073	16H	3-16	1/8 - 5/8"	J6	50.5	92	103	1070	3302-042
11074				B16	50.5	92	103	1080	3302-043
11075				B18	50.5	97	108	1090	3302-044